

56-18  
182846  
P. 22


N94-15892

# ENVISAT ASAR

J. Louet

European Space Laboratory  
The Netherlands





PRECEDING PAGE BLANK NOT FILMED

77

PAGE 76 INTENTIONALLY BLANK

## **Objectives**

**The Objectives of ASAR are to measure:**


- ♦ **Sea ice extent, character and motion**
- ♦ **Snow and ice extent and character**
- ♦ **Vegetation, Land use**
- ♦ **Surface topography**
- ♦ **Ocean waves and circulation**

**Independence of cloud cover/day or night**

**With respect to ERS-1: extended coverage and dual polarisation**

## Modes of operation

Image	"ERS" type image mode, high resolution, selectable swath position, two polarisations
Wide Swath	Wide swath with medium resolution, two polarisations
Alternating Polarisation	Alternating VV and HH operation in image mode swaths, using n samples of each polarisation
Wave	Sampled image mode. low data rate, selectable swath positions
Global Monitoring	Wide swath, low spatial resolution, low data rate, HH and VV polarisations



10 m x 1.3 m

2 m x 1.3 m

20

320

< 500 kg

< 1200 W

< 100 Mbit/s

0.89

Transmit power

Receive power

Carrier frequency

Pulse duty ratio

Pulse repetition rate

Chip rate

Beam inclination angle

Number of beam patterns

> 1.5 kW

< 3.0 dB

5.331 GHz

5.6 % (nominal)

1580 to 2150 s<sup>-1</sup>

16MHz

13.3° to 39.1°

8 Tx, 8 Rx

## ASAR PARAMETERS

PARAMETER	UNIT	IMAGE (H, V or H/V)	WIDE SWATH	GLOBAL SAR MONITORING	WAVE
SPATIAL RESOLUTION	m	30	90	900	30
SWATH WIDTH	km	100 to 56 ( 7 swaths)	405 to 420 ( 5 swaths)	405 to 420 (5 swaths)	5 x 5 (any swath)
INCIDENCE ANGLE	deg.	15-45	17-43	17-43	15-45
DC POWER CONSUMPTION	W	1200	1200	750	520
DATA RATE	Mbps	96.5	97	1.1	0.9

MISSION LIFETIME      4 YEARS  
RELIABILITY            .89



Parameter	IMAGE	WIDE SWATH	WIDE SWATH	ALTERNATING POLARIZATION	GLOBAL MONITORING
Spatial Resolution along track across track	≤ 30 m ≤ 30 m	≤ 100 m ≤ 100 m	≤ 30 m ≤ 30 m	≤ 30 m ≤ 30 m	≤ 1000 m ≤ 1000 m
Ambiguity Ratio (Point) along track across track	≥ 25 dB ≥ 31 dB	≥ 25 dB ≥ 31 dB	≥ 25 dB ≥ 31 dB	≥ 25 dB ≥ 31 dB	≥ 25 dB ≥ 31 dB
Ambiguity Ratio (Distrib.) along track across track	≥ 22 dB 13 dB below σ <sub>0</sub> min.	≥ 22 dB 13 dB below σ <sub>0</sub> min.	≥ 22 dB 13 dB below σ <sub>0</sub> min.	≥ 22 dB 13 dB below σ <sub>0</sub> min.	≥ 22 dB 13 dB below σ <sub>0</sub> min.
Radiometric Resolution	≤ 2.5 dB	≤ 2 dB	≤ 2 dB	≤ 3.5 dB	≤ 1.5 dB
Radiometric Accuracy	≤ 0.65 dB	≤ 0.65 dB	≤ 0.65 dB	≤ 0.65 dB	≤ 0.65 dB
Swath Width	up to 100 km	400 km	5 km	up to 100 km	400 km

## BACKSCATTER MODEL


<i>Incidence Angle (degrees)</i>	<i>Sigma Naught value (dB)</i>
10	-10
20	-14
30	-17
40	-20
45	-22
50	-24.4
55	-26.2
60	-27.6

# COMPARISON ASAR-AMI

## A S A R

	ERS-1 AMI	ASAR AMI SWATH	Swath 1	Swath 2	Swath 3	Swath 4	Swath 5	Swath 6	Swath 7
Incidence Angle mid swath	23°	23°	18.8°	22.8°	28.7°	33.7°	37.7°	41.1°	44.0°
Swath Width	80 km	80 km	100 km	100 km	80 km	85 km	65 km	70 km	55 km
Nominal Spatial Resolution	30 m	30 m	30 m	30 m	30 m	30 m	30 m	30 m	30 m
Achievable Spatial Resolution (range)	30 m	30 m	30 m	24 m	19.5 m	17 m	15 m	15 m	13.5 m
Signal to Noise Ratio (worst case) (ø0-18dB, nom.res.)	7.0	5.0 dB(1)	5.5 dB	4.8 dB	5.5 dB	4.8 dB	4.2 dB	7.47 dB	8.65 dB
Polarisation	VV	HH,VV	HH,VV	HH,VV	HH,VV	HH,VV	HH,VV	HH,VV	HH,VV

# Instrument Design and Technology




■ Distributed transmit/receive modules employing integrated microwave technology for dynamic and adaptive beamforming


■ Digital chip generation, for maximizing pulse duty ratio

■ Online instrument calibration

**Tx and Rx beams independently controllable to achieve flexible swath coverage**




**TILE**






ANTENNA IS  
COMPOSED OF 20 TILES

EACH TILE IS COMPOSED OF :

- 1 RADIATING PANEL
- 16 T/R MODULES
- 4 POWER SUPPLY UNITS
- 1 TILE CONTROLLER INTERFACE UNIT
- 1 RX/TX CORPORATE FEED
- 1 CALIBRATION CORPORATE FEED



## TRANSMIT / RECEIVE MODULE



320 modules on the antenna,  
each of which can provide :

**In Transmit :**

**Output of 8W**

**Phase control on 360° by 5-6 steps**

**On Receive :**

**Noise figure of 3dB**

**20dB dynamic range by 0.5dB step.**

**Phase control on 360° by 5-6 steps**


**Dimensions :**

**266x38.8x31.4mm3 (l x w x h)**

**Mass :**

**170g**






15/09/92  
T/R MODULE  
IT-1-4576





# ASAR C-band Microstrip Patch Antenna Design



C-2

## **DATA RATES**

**IMAGE SINGLE SWATH (H, V or ALTERNATE H&V) < 100 Mbps**


**WIDE SWATH (>400Km) < 100 Mbps**

**WAVE MODE 900 Kbps**


**GLOBAL SAR MODE 1100 Kbps**

**WAVE & GLOBAL SAR MODE ARE ON BOARD RECORDED,  
FOR ALL OTHER ASAR MODES DIRECT TRANSMISSION X BAND AND/OR  
KA BAND VIA EUROPEAN DRS SYSTEM.**


# ASAR WIDE SWATH COVERAGE WITHIN 1 DAY



**ASAR WIDE SWATH COVERAGE  
WITHIN 2 DAYS**



# ASAR WIDE SWATH COVERAGE WITHIN 3 DAYS



# ASAR Programme

